



**PBI**

**PORTERET BEAULIEU INDUSTRIE**

**21310 BEZOUOTTE**

**FRANCE**

Tel : ( 33 ) 3 80 10 08 08

Fax : ( 33 ) 3 80 36 56 87

**GLASS TEXTILES  
TAPES**

**CHEMICAL COMPOSITION :**

E-glass fibre :

SiO<sub>2</sub> 55 %

CaO 21 %

Al<sub>2</sub>O<sub>3</sub> 15 %

B<sub>2</sub>O<sub>3</sub> 8 %

Others 1 %

**CHARACTERISTICS :**

Maximum service temperature is 500 °C

Colour : white

Thickness : 2, 3, and 5 mm ( ± 10 % )

Width : 20, 30, 40, 50, 60, 80, 100 and 120 mm for 2 and 3 mm thick  
20, 30, 40, 50, 60, 80 mm for 5 mm thick

Length of the roll : 25 m ( for any width or thickness )

*Notes* : ability to make ladder tape or tape with adhesive.

**APPLICATIONS :**

Fireproof wrapping of flexible tubings.

Insulation of industrial chimneys.

The information contained herein is based upon data considered to be accurate. However, no warranty is expressed or implied regarding the accuracy of these data, and the results to be obtained from the use thereof. This information is furnished as a guide only and upon the condition that the person receiving it shall make tests to determine the accuracy and suitability for his or her own purpose.